




Dimensions in mm



Référence	12NC	Lampe (W)	Culot	U.E.
DC 400TULIPE CL II	9105015457 18	Standard 75W / PL E-C 15W	E27	1
DC 500TULIPE CL II	9105015458 18	Standard 75W / PL E-C 20W	E27	1

FR Application

- Animation et éclairage de voies piétonnes.
- Chemins.
- Espaces verts, etc.

Description

- Boule claire en méthacrylate (PMMA) haute densité stabilisée contre les U.V.
- Console en polycarbonate noir renforcé de fibres de verres.
- Lampe standard 75W ou économique PL E-C 15-20W.
- Diamètres (Ø): 400 mm, 500 mm.
- Douille E27 en porcelaine.
- Alimentation: 230V/50Hz.
- Emmanchement sur fût: Ø 60 mm.

Maintenance

- Accès à la lampe après démontage du diffuseur.

UK Application

- Liveliness and lighting of pedestrian walks.
- Walkways.
- Green areas, etc.

Description

- Methacrylate (PMMA) clear globe of high stabilised density against U.V.
- Fibreglass reinforced black polycarbonate bracket.
- Standard 75W or economical PL E-C 15-20W lamps.
- Diameters (Ø): 400 mm, 500 mm.
- Porcelain E27 lamp socket.
- Power supply: 230V 50Hz.
- Shaft fitting: Ø 60 mm.

Maintenance

- Lamp access after diffuser removal.