

HO3 VVH2 - F

BT DOMESTIQUE
NFC 32-201-5

300/300 V
NT 88-07

LV DOME-STIC
IEC 60 227-5

CONSTITUTION

1 - Ame : Cuivre souple

2 - Isolation : PVC

3 - Gaine : PVC

CARACTERISTIQUES

Tension nominale : 300/300 V

Conducteur : cuivre souple classe 5 (p 32)

Température max. admissible :

70° C En permanence

150° C En court-circuit

Repérage des conducteurs :

Brun - bleu

UTILISATION

Ces câbles sont destinés à l'alimentation des appareils électro-domestiques. En cas de flexion ou de torsion répétées, il est recommandé d'utiliser les câbles ronds HO3VV-F.

CONSTRUCTION

1- Conductor : Flexible copper

2- insulation : PVC

3- Sheath : PVC

CHARACTERISTICS

Rated voltage : 300/300 V

Conductor : Flexible copper class 5 (p 32)

Max. permissible temperature :

70° C Operating T°

150° C Short-circuit T°

Conductor identification :

Brown - blue

USE

These cables are used to supply small household appliance with power.

In repeated cases of bending or twisting stress, it is advisable to use a round cable HO3VV-F.



Passable
Average



- 15° C
+ 60° C



Mediocre
Poor



Très Bon
Very good



Mediocre
Poor



Passable
Average



Bon
Good

H03 VVH2 - F

Section	Dimension maxi extérieur	Intensité à l'air libre 30°C
Cross Section	Outer dimension max.	Current rating in air 30°C
mm ²	mm	A
2 x 0,5	3,7 x 5,9	13
2 x 0,75	3,8 x 6,3	14